

LT5D093 / LT5D123 / LT5D185

LT5D255 / LT5D325



Número de parte		LT5D093-110V	LT5D123-110V	LT5D185-110V	LT5D255-110V	LT5D325-110V
		LT5D093-230V	LT5D123-230V	LT5D185-230V	LT5D255-230V	LT5D325-230V
		LT5D093-400V	LT5D123-400V	LT5D185-400V	LT5D255-400V	LT5D325-400V
Características		• Rango de corriente de operación: 7 a 32A • Voltaje de operación: 690V • Voltaje de aislamiento: 690V • Resistencia a sobre tensiones: ≥6000V • Grado de protección: IP44 • Cubierta: plástico resistente a rayos UV y auto extingible • Temperatura de operación: -10°C a 65°C				
Corriente nominal		9 A	12 A	18 A	25 A	32 A
Voltaje de bobina		110V CA	110V CA	110V CA	110V CA	110V CA
		230V CA	230V CA	230V CA	230V CA	230V CA
		400V CA	400V CA	400V CA	400V CA	400V CA
Capacidad nominal (kW) de motores 50/60Hz categoría AC-3	220V 230V	2.2	3	4	5.5	7.5
	380V 400V	4	5.5	7.5	11	15
	415V 440V	4	5.5	9	11	15
Rango de ajuste de relevador de sobrecarga		7 .. 10A	9 .. 13A	12 .. 18A	17 .. 25A	23 .. 32A

NOTA: Bajo pedido se puede cambiar el relevador de sobrecarga para modificar el rango de ajuste.

Dimensiones (mm)

