



Features :

- Auto / Manual Mode Selection
- Failsafe / Non-failsafe Mode Selection
- Self Check Mode
- Remotely Controllable

Certifications : **CE**

Display Specifications

LED Indication	1. YELLOW : Power ON Indication 2. RED : Relay Status 3. Green LEDs : Healthy State Indication in Manual Mode
----------------	---

Input Specifications

Sensor type	PTC
-------------	-----

Output Specifications

Type of contact	DPDT
Contact rating	8A 250VAC
Contact material	AgSnO ₂
Max switching current	8A
Electrical life	1x10 ⁵ Operations
Mechanical life	1x10 ⁷ Operations

Functional Specifications

Relay operating mode	Failsafe mode Non-failsafe mode
----------------------	------------------------------------

Sensor Specifications

Sensor Short	: ≤ 40
Sensor Healthy	: ≥ 44Ω (±3Ω) to <3.8KΩ(±150Ω)
Sensor Trip	: ≥3.8KΩ (±150Ω) to <5.5KΩ (±150Ω)
Sensor Open	: ≥5.5KΩ (±150Ω) & Above
Sensor Cut-in / Recovery	: ≤1.5KΩ (±60Ω)

Auxiliary Supply Specifications

Supply Voltage	95-270V AC / DC
Frequency	50-60 Hz
Power consumption	Approx. 3 Watts @ 230VAC
Initialization time	3 seconds

Environmental Specifications

Temperature	Operating : 0° to 50° C Storage : -20 to 70° C
Humidity (non-condensing)	10% to 95% RH

Mechanical Specifications

Mounting	Din Rail Mounting (size 35mm)
Type of connection	Terminal screw - 16A rating
Dimension	60 x 35 x 90mm
Housing	2M
Weight	115 g
Type of protection	IP20
No of terminals	11 (L, N, REMOTE, GND, PTC, NO1, NC1, C1, NO2, NC2, C2)

Ordering Information

PRODUCT CODE	OUTPUT 1	SUPPLY VOLTAGE	CERTIFICATION
TPRA2M1-1-U-CE	RELAY	95-270V AC / DC	CE